



CAP. TONS	SPAN L	A	F	W.B.	BRIDGE WEIGHT LBS.	MAX. WHEEL LOAD LBS.	GIRDER SIZE	Bridge HP.
5	20'-0"	6'-11"	1'-7"	5'-3"	2400	5200	W14x68	(2) x 0.4/0.1 3600/900 RPM
	24'-0"	6'-11"	1'-7"	5'-3"	2800	5450	W14x68	
	28'-0"	6'-11"	1'-7"	5'-3"	3400	5700	W14x68	
	32'-0"	6'-11"	1'-9"	5'-3"	3750	5850	W16x77	
	36'-0"	8'-2"	1'-9"	6'-6"	4500	6100	W16x89	(2) x 0.9/0.2 3600/900 RPM
	40'-0"	8'-2"	1'-11"	6'-6"	5250	6300	W18x106	
	44'-0"	8'-2"	1'-11"	6'-6"	6000	6550	W18x119	
	48'-0"	10'-2"	2'-2"	8'-6"	7200	6900	W21x132	
	52'-0"	10'-2"	2'-2"	8'-6"	8350	7200	W21x147	
	56'-0"	10'-2"	3'-0"	8'-6"	9000	7400	Box	
60'-0"	10'-2"	3'-1"	8'-6"	10400	7750	Box		

	TROLLEY MODEL *		
	3111D-1423	3111D-2423	3111D-3423
LIFT	21'-0"	29'-10"	37'-0"
TROLLEY WEIGHT	781 LBS.	838 LBS.	887 LBS.
DIM. E	3'-0"	3'-6"	4'-0"

* Longer Lifts Available

HOISTING SPEED	16/4 FPM
BRIDGE SPEED	80/20 FPM
TROLLEY SPEED	67/15 FPM
RUNWAY RAIL	30# ASCE
POWER SUPPLY	460-3-60
WHEEL DIA.	6.3"

MUNCK

PRODUCT
INFORMATION

TOP RUNNING
SINGLE GIRDER CRANE

5 TON CAPACITY

DWG. NO:

17534101

DATE: 02/02/02

REVISION: 1

DWN. BY:

CHK. BY:

APP. BY: