



CAP. TONS	SPAN L	A	F	W.B.	BRIDGE WEIGHT LBS.	MAX. WHEEL LOAD LBS.	GIRDER SIZE	Bridge HP.
10	20'-0"	8'-5"	2'-0"	6'-6"	6000	12500	W14x61	(2) x 0.9/0.2 3600/900 RPM
	24'-0"	8'-5"	2'-1"	6'-6"	7500	12950	W14x68	
	28'-0"	8'-5"	2'-2"	6'-6"	9000	13400	W16x77	
	32'-0"	8'-5"	2'-4"	6'-6"	10500	13850	W18x97	
	36'-0"	8'-5"	2'-5"	6'-6"	12000	14300	W21x111	(2) x 1.2/0.3 3600/900 RPM
	40'-0"	8'-5"	2'-6"	6'-6"	13500	14750	W21x132	
	44'-0"	8'-5"	2'-7"	6'-6"	15000	15200	W24x84 w/C15x33.9	
	48'-0"	10'-5"	2'-8"	8'-6"	16500	15650	W24x94 w/C15x33.9	
	52'-0"	10'-5"	2'-9"	8'-6"	18000	16100	W27x102 w/C15x33.9	
	56'-0"	10'-5"	2'-10"	8'-6"	19500	16550	W27x114 w/C15x33.9	
60'-0"	10'-5"	2'-11"	8'-6"	21000	17000	Box		

	TROLLEY MODEL *		
	3122B-1426	3122B-2426	3122B-3426
LIFT	21'-3"	29'-2"	40'-0"
TROLLEY WEIGHT	1400 LBS.	1450 LBS.	1500 LBS.

* Longer Lifts available

HOISTING SPEED	16/5 FPM
BRIDGE SPEED	80/20 FPM
TROLLEY SPEED	67/16 FPM
RUNWAY RAIL	40# ASCE
POWER SUPPLY	460-3-60
WHEEL DIA.	9.8"



PRODUCT INFORMATION

TOP RUNNING DOUBLE GIRDER CRANE

10 TON CAPACITY

DWG. NO:

17534503

DATE: 02/02/02

REVISION: 2

DWN. BY:

CHK. BY:

APP. BY: